

MTH Hose

Stainless Steel flexible hose lined with Smooth Bore PTFE Liner

304SS flexible metal hose lined with smooth PTFE liner and flared thru standard end fittings. Designed for applications requiring a large diameter smooth bore flexible hose combining the unexcelled corrosion resistance and sanitary properties of PTFE and the durability of flexible metal hose. This smooth bore hose is specified and used in an endless variety of applications where the conditions of service are beyond the capabilities of rubber, synthetic or metal hose alone. The PTFE smooth bore I.D.'s minimize pressure drop. MTH is available with virgin PTFE liner.

MTH Advantage:

Corrosion Resistant- PTFE is fully resistant to the broadest range of industrial chemicals and has a zero corrosion rate, lower life cycle costs and is Non-contaminating.

Cleanable - Non-Stick, low porosity tube does not trap bacteria, and can be readily cleaned with steam, detergents, caustics or solvents.

Sanitary – FDA approved materials meet or exceed **3A** requirements.

Compatible - Will not contaminate or impart a taste, color or odor to any media.

Durable - Designed for extended use in hostile environments involving severe chemical, thermal and mechanical stresses. Does not suffer aging or embrittlement, even with extreme thermal cycling.

Double containment - Metal housing is a secondary containment vessel.

PTFE "Flared-Thru" Fittings:


The thick PTFE tube passes through the end fitting and is flared radially outward against the sealing face of the fitting. This economical design creates a continuous PTFE fluid conduit. Standard fitting styles available are Flanged, Male and Female and Cam Lock. Flange materials available in Epoxy coated Carbon Steel, 304SS and 316SS.

Specifications:

Temperature Range: -65°F(-54°C) to +450°F(232°C)

I.D. NOMINAL	O.D. (in.)	WORKING PRESSURE 70°F (psi)	WORKING PRESSURE 350°F (psi)	VACUUM (in.-Hg)	MINIMUM BEND RADIUS	WEIGHT PER FT. (lbs/ft.)
1	1 1/2	765	600	29.9	12	1.2
1 ½	2 1/4	530	475	29.9	15	2.1
2	2 5/8	535	435	29.9	21	2.8
3	3 11/16	300	235	29.9	28	3.0
4	4 7/8	230	190	29.9	46	4.0
6	7 1/8	150	150	29.9	65	8.9
8	9 1/4	150	125	29.9	89	16.0
10	11 3/8	100	75	24.0	120	20





PureFlex™ Inc. information is based on technical data and testing that PureFlex™ Inc. believes to be reliable. It is intended for use by persons having technical skill, at their own discretion and risk. Since conditions of product are outside PureFlex™ Inc. control, PureFlex™ Inc. makes no warranties, express or implied, and assumes no liability in connection with any use of this information.